Utility Capstan Electric Winch-Hoist 🕂 📔 🔤 🔤

Features

- 800-lb single-line or 1,600-lb double-line lift
- 12 Volt permanent magnet motor
- Worm gear reduction for positive load holding
- Portable and rugged
- 10' pendant hand or foot control
- Capstan rope drum
- Frictionless bearings

Applications

All My-te winches and hoists are designed for material handling usage only.

Utility truck installation Overhead line crews Tower and antenna erection Transformer replacement



Construction Features:

- Heavy-duty angle base drilled for four 1/2" bolts (9/16" mounting holes) with no welding required
- Fully sealed aluminum housings, with precision-cut gears, run in an oil bath
- Hardened steel worm and forged bronze worm gear holds load in position when stopped.
- Stress-proof drum shaft
- Frictionless bearings
- 175:1

Hoisting Rope:

Consult your local dealer for type and size of rope. Maintain at least three wraps of rope on capstan drum when in use. Heavier loads may require four wraps of rope.

Power:

- Reversible permanent magnet 12 Volt motor
- 10 amp No load
- 100 amp Full load

Speeds:

- 20 FPM: No-load drum speed
- 15 FPM: 500 lbs

Duty Cycle:

• 25% - 15 min/hr when operating at full load.


Shipping Weight: 66 lbs

Factory-Installed Options:


- Foot switch
- High speed gears
- Pole mount
- Swivel mount
- Receiver hitch mount

For custom design and application assistance of a My-te winch-hoist, see your My-te distributor or call My-te Products, Inc. (800) 840-9880. Visit us at WWW.myte.com

- FRONT VIEW



- TOP VIEW



- SIDE VIEW

